

	SQ110R	SQ120R	SQ166R	SQ175
BTU				
80/80/80	91,000	110,000	126,000	143,000
80/80/63	87,000	103,000	120,000	134,000
80/50/63	61,000	72,000	82,000	90,000
Coefficient of Performance				
80/80/80	5.5	5.5	5.6	6.1
80/80/63	5.3	5.3	5.3	5.7
80/50/63	4.0	4.0	4.0	4.0
Operates down to °F	mid to low 20s	mid to low 20s	mid to low 20s	mid to low 40s
Refrigerant	R410A	R410A	R410A	R410A
Electrical				
Heat or Heat & Cool	H & C	H & C	H & C	H
kW Input	4.8	5.9	6.6	6.9
Voltage/Hz/Phase	208-230/60/1	208-230/60/1▲	208-230/60/1▲	208-230/60/1▲
Minimum Circuit Ampacity	40.0	38.4	41.4	42.0
Minimum/Maximum Fuse Size	40/60	40/60	50/60	50/60
Water Flow				
Minimum/Maximum (gpm)	30/70	30/70	30/70	30/70
Physical				
Weight (lbs)	257	257	268	328
Size (lengthxwidthxheight)	37"x34"x41"	37"x34"x41"	37"x34"x45"	37"x34"x45"
Shipping				
Weight (lbs)	315	315	329	390
Size (lengthxwidthxheight)	40"x36"x46"	40"x36"x46"	40"x36"x50"	40"x36"x50"
Sound Level Decibels at 10 ft.	55 dB	55 dB	55 dB	55 dB

Rated in accordance with ARI standard 1160 water temp/ambient air/relative humidity

▲ - also available in 3 phase units - visit our website for details